

UK Declaration of Performance

No. 20-1000_002-2026



1. Unique identification of the product-type
2. Type, batch or serial number or other element allowing identification of the construction product
3. Intended use or uses of the construction product as foreseen by the manufacturer
4. Name, registered trade name or trade mark and contact address of the manufacturer
5. System of assessment and verification of constancy of the construction products
6. Name and identification number of the Approved Body concerning a construction product covered by a designated standard
7. Declared performance according to

Single Skin Steel Profiled Sheet

20/1000 Liner Profile (With Swages), in Over Purlin (Forward) and Under Purlin (Reverse) Configurations

Single skin steel profiled sheet for use as internal lining (liner) of buildings in accordance with EN 14782:2006

BRIARWOOD PRODUCTS LTD,
Briarwood Business Park,
Commerce Way,
Walrow Industrial Estate,
Highbridge, Somerset, TA9 4AG

AVCP System 4

The manufacturer has taken responsibility for initial type testing and implementation of factory production control, in accordance with AVCP System 4

BS EN 14782:2006
Self-supporting metal sheet for roofing, external cladding and internal lining - Product specification and requirements.

See the below tables showcasing the performances of each product using materials which we roll from.

UK CA BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 20/1000 Liner, Thickness: 0.50, Class 1, S220GD + Z225 or AZ150 Side 1: Polyester 25µm, Side2: EP7µm, EN508-1 Mechanical Resistance: Roof Wall Resistance to concentrated force No Performance Declared No Performance Declared Water Permeability: No Performance Declared Dimensional Change: No Performance Declared Release of Regulated Substances: No Performance Declared External Fire Performance: NPD Broof t4 Reaction to Fire: C-s3, d0 C-s3, d0 Durability: No Performance Declared	UK CA BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 20/1000 Liner, Thickness: 0.70, Class 1, S220GD + Z225 or AZ150 Side 1: Polyester 25µm, Side2: EP7µm, EN508-1 Mechanical Resistance: Roof Wall Concentrated force 1.2kN, span NPD 2.5m Water Permeability: No Performance Declared Dimensional Change: No Performance Declared Release of Regulated Substances: No Performance Declared External Fire Performance: NPD Broof t4 Reaction to Fire: C-s3, d0 C-s3, d0 Durability: No Performance Declared	UK CA BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 20/1000 Liner, Thickness: 0.50, Class 1, S220GD + Z225 or AZ150 Side 1: Generic Plastisol 200µm, Side2: EP7µm, EN508-1 Mechanical Resistance: Roof Wall Resistance to concentrated force No Performance Declared No Performance Declared Water Permeability: No Performance Declared Dimensional Change: No Performance Declared Release of Regulated Substances: No Performance Declared External Fire Performance: NPD Broof t4 Reaction to Fire: C-s3, d0 C-s3, d0 Durability: No Performance Declared	UK CA BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 20/1000 Liner, Thickness: 0.70, Class 1, S220GD + Z225 or AZ150 Side 1: Generic Plastisol 200µm, Side2: EP7µm, EN508-1 Mechanical Resistance: Roof Wall Concentrated force 1.2kN, span NPD 2.5m Water Permeability: No Performance Declared Dimensional Change: No Performance Declared Release of Regulated Substances: No Performance Declared External Fire Performance: NPD Broof t4 Reaction to Fire: C-s3, d0 C-s3, d0 Durability: No Performance Declared
---	--	--	---

The performance of the product(s) identified in point 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.



Oliver Janes - CEO
Somerset, England, UK
Date signed: 30/09/2026